



[Zoom in Picture](#)

■ Features

- Surge protection and optical isolation
- RS 422/485 DB9 male ports
- Speed up to 921.6kbps
- no external power supply

VScom USB-COM-I SI

Quick Link: | [Features](#) | [Overview](#) | [Hardware Specifications](#) | [Ordering Information](#) |

■ Overview

Isolated industrial serial ports on USB connect RS-422 and RS485 devices, used in industrial environment. With RS-485 the data direction is controlled by the port, without further action from the software.

The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.

■ Hardware Specifications

| | |
|--------------------------|---|
| Ports | One RS422/485 port |
| Speed | up to 921.6kbps |
| RS422/485 signals | RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND |
| Power | USB bus powered, no external power supply |
| Driver | Windows 98, ME, 2000, XP, 2003 Server Linux (Kernel 2.4 and up built-in) |
| Connectors | one DB9 male |
| Environment | surge protection and optical isolation |

[>Back to top](#)

■ Ordering Information

| | |
|---------------------|---|
| Art.No | 623 |
| Product Name | VScom USB-COM-I SI |
| Packing list | VScom USB-COM-I SI Adapter USB cable 0,9m CD, English Documentation |

[>Back to top](#)

■ Full size product image



[>Back to top](#)